

Approval body for construction products
and types of construction

Bautechnisches Prüfamt

An institution established by the Federal and
Laender Governments

★ ★ ★
★ Designated
according to
Article 29 of Regula-
tion (EU) No 305/2011
and member of EOTA
(European Organi-
sation for Technical
Assessment)
★ ★ ★
★ ★

European Technical Assessment

ETA-08/0262
of 17 October 2017

English translation prepared by DIBt - Original version in German language

General Part

Technical Assessment Body issuing the
European Technical Assessment:

Trade name of the construction product

Product family
to which the construction product belongs

Manufacturer

Manufacturing plant

This European Technical Assessment
contains

This European Technical Assessment is
issued in accordance with Regulation (EU)
No 305/2011, on the basis of

This version replaces

Deutsches Institut für Bautechnik

SFS intec Flat Roof Fasteners

Fasteners for flexible roof waterproofing systems

SFS intec AG
FasteningSystems
Rosenbergsaustraße 10
9435 HEERBRUGG
SCHWEIZ

Factory 1 to factory 15, factory 18 to factory 23

114 pages including 109 annexes which form an integral
part of this assessment

ETAG 006,
used as EAD according to Article 66 Paragraph 3 of
Regulation (EU) No 305/2011.

ETA-08/0262 issued on 25 April 2013

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

Specific Part

1 Technical description of the product

The construction products are mechanical fasteners. The fasteners comprise a screw, blind rivet or anchor made of coated carbon steel, aluminium or stainless steel and a washer with or without integrated sleeve. The washers without integrated sleeve are made of coated carbon steel whereas the washers with integrated sleeve are made of polypropylene or polyamide. Some fasteners include a perforated lath made of coated carbon steel.

The fasteners are shown in the Annexes to this ETA.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The fasteners are intended to be used for the fastening of flexible roof waterproofing membranes according to ETAG 006. The possible substrates are steel or aluminium decks, concrete, aerated concrete, pumice panel or timber.

The performances given in Section 3.2 are only valid if the fasteners are used in compliance with the specifications and conditions given in sections 3.1 and 3.3 and the Annexes to this ETA.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the fasteners of at least 10 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

In order to use the fasteners for systems of mechanically fastened flexible roof waterproofing membranes according to ETAG 006 a separate ETA is necessary for the entire roof waterproofing system. The system ETA covers the wind uplift resistance of the entire system as well as the product characteristics of the components of the system.

3 Performance of the product and references to the methods used for its assessment

3.1 Characteristics of the product

The fasteners shall correspond to the information given in Annexes 1 to 94.

Corrosion resistance of blind rivet's mandrel type TPR-L shall be provided by minimum 8 µm galvanisation.

The material properties, dimensions and tolerances not indicated in Annexes 1 to 94 shall correspond to the information laid down in the technical information¹ to this European technical assessment.

3.2 Safety and accessibility in use (BWR 4)

| Essential characteristic | Performance |
|---|-----------------------------------|
| Characteristic tensile loading | See Annexes 95 to 109 |
| Resistance to unwinding | pass |
| Resistance to corrosion of metallic fasteners | pass; ≤ 15 % surface corrosion |

¹

The technical documentation is deposited with Deutsches Institut für Bautechnik and as far as relevant for the tasks of the approved bodies involved in the attestation of conformity procedure is handed over to the approved bodies.

| Essential characteristic | Performance |
|---|---|
| Impact resistance and brittleness of plastic fasteners (before and after heat ageing) | pass; drop height > 1,0 m |
| Requirements for results of Charpy tests for plastic materials (before and after heat ageing) | pass; not any significant decline compared to the results before heat ageing |

The thickness and strengths of the materials listed in the tables of characteristic tensile loads (Annexes 95 to 109) are minimum requirements. The values given are also applicable for materials with higher thickness and strengths. The values of axial loading shown in Annexes 95 to 109 were determined by axial loading tests according to ETAG 006.

The fasteners are deemed to satisfy the requirements of ETAG 006 concerning unwinding. This was evaluated on the basis of the existing field experience of the manufacturer.

The durability requirements of ETAG 006 (resistance to corrosion of metallic fasteners, impact resistance and brittleness of plastic fasteners before and after heat ageing, requirements for results of Charpy tests for plastic materials before and after heat ageing) are satisfied for the coated carbon steel, aluminium, stainless steel, polypropylene and polyamide components of the fasteners.

All coated carbon steel components resisted to 15 cycles of the test procedure described in ETAG 006 (Kesternich test) and did not show more than 15 % surface corrosion.

The test results of the tests to check the impact resistance and brittleness of the polyamide and polyethylene components showed a drop height of more than 1.0 m before and after heat ageing of these components. Furthermore the results of the corresponding Charpy tests after heat ageing did not show any significant decline compared to the results before heat ageing.

3.3 Indications concerning installation

The installation is solely carried out according to the manufacturer's instructions. When assembling the fastener's components the screw thread penetrating into the substrate shall not be damaged. The manufacturer hands over the assembly instructions to the assembler.

The conformity of the installed fastener with this ETA is attested by the executing company.

It is in the responsibility of the manufacturer to ensure that the information on the specific conditions according to 1, 2, 3.1 and 3.2 is given to those who are concerned. The information may be given by reproduction of the ETA. In addition all installation data shall be shown clearly on the package and/or on an enclosed instruction sheet, preferably using illustration(s).

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with ETAG 006 the applicable European legal act is: 1998/143/EC.

The system to be applied is: 2+




5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.





Issued in Berlin on 17 October 2017 by Deutsches Institut für Bautechnik





Dr.-Ing. Lars Eckfeldt
p. p. Head of Department

beglaubigt:
Reimuth





| Combination 1A IR2-4,8 / IR-82x40 | Combination 1B IR2-4,8 / IF-70x70 |
|--|--|
| <p>IR-82x40</p>  | <p>IF-70x70</p>  |
| <p>IR2-4,8</p>  | <p>IR2-4,8</p>  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 1</p> | |

English translation prepared by DIBt

| Combination 2A IR2-S-4,8 / IR-82x40 | Combination 2B IR3-4,8 / IR-82x40 |
|--|---|
| <p>IR-82x40</p>  | <p>IR-82x40</p>  |
| <p>IR2-S-4,8</p>  | <p>IR3-4,8</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 2</p> |

| Combination 3A IR2-C-4,8 / IRC/W-82x40 | Combination 3B BS-4,8 / RP45 |
|--|--|
| <p>IRC/W-82x40</p>  | <p>RP45</p>  |
| <p>IR2-C-4,8</p>  | <p>BS-4,8</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 3</p> |

English translation prepared by DIBt

| Combination 4A BS-4,8 / R45 | Combination 4B BS-4,8 / R75 |
|---|--|
|  |  |
|  |  |
| SFS intec flat roof fasteners | Annex 4 |


| Combination 5A BS-4,8 / RP75 | Combination 5B BS-4,8 / TPS |
|---|---|
| <p>RP75</p> <p>Dimensions: Ø 9,5, Ø 5,2, Ø 73, L, Ø 13,6.</p> | <p>TPS</p> <p>Dimensions: Ø 11, 43, Ø 5,6, 76, L, Ø 15,1.</p> |
| <p>BS-4,8</p> <p>Dimensions: T25, Ø 8,8, 75, L, Ø 4,9.</p> | <p>BS-4,8</p> <p>Dimensions: T25, Ø 8,8, 75, L, Ø 4,9.</p> |
| SFS intec flat roof fasteners | Annex 5 |

English translation prepared by DIBt





| Combination 6A BS-4,8 / TPP | Combination 6B BS-4,8 / R48-3N |
|---|-----------------------------------|
| | |
| | |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 6</p> | |





English translation prepared by DIBt





Combination 7A
BS-4,8 / RP48-3N







Combination 7B
BS-4,8 / SH-18/65 / Protan steelbar







| Combination 8A BS-S-4,8 / RP45 | Combination 8B BS-S-4,8 / TPP |
|---|--|
|  |  |
|  |  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 8</p> | |

| Combination 9A BS3-4,8 / RP45 | Combination 9B BS-6,1 / R45 |
|--|--|
| <p>RP45</p>  | <p>R45</p>  |
|  |  |
| SFS intec flat roof fasteners | Annex 9 |





| Combination 10A IFP2-6,7 / IRP-82x40 | Combination 10B BS-6,7 / R45 |
|--|---------------------------------|
| <p>IRP-82x40</p> <p>IFP2-6,7</p> <p>BS-6,7</p> | <p>R45</p> |





| Combination 11A BS-6,7 / R75 | Combination 11B BS-6,7 / TPS |
|---|--|
|  |  |
|  |  |
| SFS intec flat roof fasteners | Annex 11 |

| Combination 12A BS-S-6,7 / R45 | Combination 12B BS-S-6,7 / R75 |
|--------------------------------------|-----------------------------------|
| | |
| | |
| SFS intec flat roof fasteners | Annex 12 |




| Combination 13A BS-S-6,7 / TPS | Combination 13B TPR-L-6,3 / IRD-82x40 |
|---|---|
|  |  |
|  |  |
| SFS intec flat roof fasteners | Annex 13 |





| Combination 14A IG-6,0 / IRD-82x40 | Combination 14B TS-T25-6,0 / R45 |
|--|--|
| <p>IRD-82x40</p> <p>Technical drawings showing the profile and top view of the IRD-82x40 fastener. The profile view shows a total height of 7,5 mm and a shank diameter of Ø 7,5 mm. The top view shows a base width of 82 mm and a thickness of 40 mm.</p> <p>IG-6,0</p> <p>Technical drawings showing the profile and top view of the IG-6,0 screw. The profile view shows a total length L and a shank diameter of Ø 10,5 mm. The top view shows a head diameter of Ø 8 mm and a base diameter of Ø 6 mm.</p> | <p>R45</p> <p>Technical drawings showing the profile and top view of the TS-T25-6,0 fastener. The profile view shows a total length L and a shank diameter of Ø 15,1 mm. The top view shows a head diameter of Ø 11 mm and a base diameter of Ø 5,6 mm.</p> <p>TS-T25-6,0</p> <p>Technical drawings showing the profile and top view of the TS-T25-6,0 screw. The profile view shows a total length L and a shank diameter of Ø 6,0 mm. The top view shows a head diameter of Ø 9,7 mm and a T25 torque setting.</p> |

| Combination 15A IWF-5,2 / MW-40-FH | Combination 15B IW-T-5,0 / IRC/W-82x40 |
|---|--|
|  |  |
|  |  |
| SFS intec flat roof fasteners | Annex 15 |





| Combination 16A IW-S-5,0 / IRC/W-82x40 | Combination 16B LBS-S-T25-8,0 / R45 |
|--|---|
| <p>IRC/W-82x40</p>  | <p>R45</p>  |
| <p>IW-S-5,0</p>  | <p>LBS-S-T25-8,0</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 16</p> |




| Combination 17A LBS-T25-8,0 / MW-40-LBS | Combination 17B LBS-T25-8,0 / R45 |
|--|--------------------------------------|
| <p>MW-40-LBS</p> <p>LBS-T25-8,0</p> | <p>R45</p> |




| Combination 18A LB-45 | Combination 18B FB-S-T25-7,5 / R45 |
|--|--|
|  |  |
| |  |
| SFS intec flat roof fasteners | Annex 18 |

| Combination 19A DT-4,8 / IRD-82x40 | Combination 19B DT-4,8 / IF/IG-C-82x40 |
|---|--|
| <p>IRD-82x40</p>  | <p>IF/IG-C-82x40</p>  |
| <p>DT-4,8</p>  | <p>DT-4,8</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 19</p> |





| Combination 20A DT-4,8 / IW-82x40 | Combination 20B DT-4,8 / R45 |
|---|---------------------------------|
| <p>IW-82x40</p> <p>SES IW</p> <p>DT-4,8</p> | <p>R45</p> |





| Combination 21A DT-S-4,8 / IRD-82x40 | Combination 21B DT-S-4,8 / IF/IG-C-82x40 |
|---|---|
| <p>IRD-82x40</p>  | <p>IF/IG-C-82x40</p>  |
| <p>DT-S-4,8</p>  | <p>DT-S-4,8</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 21</p> |





| Combination 22A DT-S-4,8 / R45 | Combination 22B DT-6,3 / IRD-82x40 |
|---|---|
| <p>R45</p>  | <p>IRD-82x40</p>  |
|  |  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 22</p> |







| Combination 23A DT-6,3 / IF/IG-C-82x40 | Combination 23B DT-S-6,3 / IRD-82x40 |
|---|---|
| <p>IF/IG-C-82x40</p>  | <p>IRD-82x40</p>  |
| <p>DT-6,3</p>  | <p>DT-S-6,3</p>  |
| SFS intec flat roof fasteners | Annex 23 |

English translation prepared by DIBt






| Combination 24A DT-S-6,3 / IF/IG-C-82x40 | Combination 24B TI-6,3 / IRD-82x40 |
|--|---|
| <p>IF/IG-C-82x40</p>  | <p>IRD-82x40</p>  |
| <p>DT-S-6,3</p>  | <p>TI-6,3</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 24</p> |

| Combination 25A TI-6,3 / IF/IG-C-82x40 | Combination 25B TI-6,3 / ID-70x70 |
|---|---|
| <p>IF/IG-C-82x40</p>  | <p>ID-70x70</p>  |
| <p>TI-6,3</p>  | <p>TI-6,3</p>  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 25</p> | |








| Combination 26A TI-T25-6,3 / R75 | Combination 26B TI-T25-6,3 / TPS |
|--|-------------------------------------|
| <p>R75</p>  <p>TPS</p>  | |
|   | |

| Combination 27A TI-T25-6,3 / R48-3N | Combination 27B TI-T25-6,3 / R45 |
|---|---|
|  |  |
|  |  |
|  |  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 27</p> | |

English translation prepared by DIBt





| Combination 28A TIA-T25-6,3 / R45 | Combination 28B BS-4,8 / Sarnafast Tube SFT-50 |
|--|---|
| <p>R45</p>  | <p>Sarnafast Tube SFT-50</p>  |
|   |   |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 28</p> |






English translation prepared by DIBt

| Combination 29A BS-4,8 / Sarnabar Tube SBT-20 / Sarnabar | Combination 29B BS-S-4,8 / Sarnafast Tube SFT-50 |
|---|--|
| <p>Sarnabar Tube SBT-20</p>   | <p>Sarnafast Tube SFT-50</p>  |
|   |   |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 29</p> |






English translation prepared by DIBt






| Combination 30A BS-S-4,8 / Sarnabar Tube SBT-20 / Sarnabar | Combination 30B Sarnafast SF-4,8 / Sarnafast KT-82x40 |
|--|---|
| <p>Sarnabar Tube SBT-20</p> <p>Technical drawing of Sarnabar Tube SBT-20. Top: Cross-section showing outer diameter Ø 10.2 and inner hole diameter Ø 6.4. Bottom: Side view showing total length L, outer diameter Ø 19.8, and inner hole diameter Ø 13.</p> | <p>Sarnafast KT-82x40</p> <p>Technical drawing of Sarnafast KT-82x40. Top view shows a U-shaped base with a width of 8 and a central hole Ø 5.1. Side view shows a total length of 82 and a height of 40. The letters 'KT' are printed on the side.</p> |
| <p>BS-S-4,8</p> <p>Technical drawing of BS-S-4,8 screw. Top: Head detail showing T25 Torx slot and outer diameter Ø 8.8. Bottom: Side view showing total length L and outer diameter Ø 4.8.</p> | <p>Sarnafast SF-4,8</p> <p>Technical drawing of Sarnafast SF-4,8 screw. Top: Head detail showing outer diameter Ø 10.5 and a slot. Bottom: Side view showing total length L and outer diameter Ø 4.9. A spring is shown at the base of the screw.</p> |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 30</p> |

| Combination 31A Sarnafast SF-4,8 / Sarnafast DT-70x70 | Combination 31B Sarnafast SBF-6,0 / Sarnafast Tube SFT-50 |
|--|--|
| <p>Sarnafast DT-70x70</p>  | <p>Sarnafast Tube SFT-50</p>  |
| <p>Sarnafast SF-4,8</p>  | <p>Sarnafast SBF-6,0</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 31</p> |







| Combination 32A Sarnafast SBF-6,0 / Sarnabar Tube SBT-20 / Sarnabar | Combination 32B TI-6,3 / Sarnafast DTL-70x70 |
|---|---|
| <p>Sarnabar Tube SBT-20</p>  <p>Sarnabar</p>  | <p>Sarnafast DTL-70x70</p>  |
|  <p>Sarnafast SBF-6,0</p>  | <p>TI-6,3xL</p>  |





English translation prepared by DIBt

| Combination 33A TI-T25-6,3 / Sarnafast Tube SFT-50 | Combination 33B TI-T25-6,3 / Sarnabar Tube SBT-20 / Sarnabar |
|---|--|
| <p>Sarnafast Tube SFT-50</p>  | <p>Sarnabar Tube SBT-20</p>   |
|  |  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 33</p> |





| Combination 34A TI-S-Z10-6,3 / R45 | Combination 34B TI-S-Z10-6,3 / R75 |
|---|---|
| <p>R45</p>  <p>Ø 11</p> <p>Ø 5,6</p> <p>Ø 45</p> <p>L</p> <p>Ø 15,1</p> | <p>R75</p>  <p>Ø 11</p> <p>Ø 5,6</p> <p>Ø 73</p> <p>L</p> <p>Ø 15,1</p> |
|  |  |
| <p>TI-S-Z10-6,3</p>  <p>SQ3</p> <p>Ø 9,7</p> <p>Ø 6,3</p> <p>50</p> <p>L</p> | <p>TI-S-Z10-6,3</p>  <p>SQ3</p> <p>Ø 9,7</p> <p>Ø 6,3</p> <p>50</p> <p>L</p> |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 34</p> |





English translation prepared by DIBt

| Combination 35A IF2-6,1 / IRD-82x40 | Combination 35B IF2-6,1 / ID-70x70 |
|--|--|
|   |   |
|  |  |
| SFS intec flat roof fasteners | Annex 35 |





| Combination 36A FB-S-T25-7,5 / IRD-82x40 | Combination 36B FB-S-T25-7,5 / IF/IG-C-82x40 |
|---|--|
|  |  |
|  |  |
| SFS intec flat roof fasteners | Annex 36 |

English translation prepared by DIBt





| Combination 37A FB-S-T25-7,5 / R75 | Combination 37B IW-S-5,0 / IW-82x40 |
|---|--|
| <p>R75</p>  | <p>IW-82x40</p>  |
|  | <p>IW-S-5,0</p>  |






| Combination 38A IW-T-5,0 / IW-82x40 | Combination 38B IWF-5,2 / IW-82x40 |
|---|--|
|  |  |
|  |  |
| SFS intec flat roof fasteners | Annex 38 |





English translation prepared by DIBt






| Combination 39A BS-4,8 / FI-P-6,8 | Combination 39B BS-S-4,8 / FI-P-6,8 |
|--|---|
| <p>FI-P-6,8</p>  <p>BS-4,8</p>  | <p>FI-P-6,8</p>  <p>BS-S-4,8</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 39</p> |





| Combination 40A TI-T25-6,3 / FI-P-6,8 | Combination 40B BS-6,1 / FI-P-6,8 |
|---|---|
| <p>FI-P-6,8</p> <p>0,75</p> <p>4,0</p> <p>Ø 80</p> <p>Ø 6,8</p> <p>0,75</p> <p>4,0</p> <p>Ø 80</p> <p>Ø 6,8</p> <p>TI-T25-6,3</p> <p>T25</p> <p>Ø 9,7</p> <p>Ø 6,3</p> <p>L</p> <p>BS-6,1</p> <p>T25</p> <p>Ø 9,7</p> <p>Ø 6,0</p> <p>L</p> <p>75</p> | <p>FI-P-6,8</p> <p>0,75</p> <p>4,0</p> <p>Ø 80</p> <p>Ø 6,8</p> <p>0,75</p> <p>4,0</p> <p>Ø 80</p> <p>Ø 6,8</p> <p>TI-T25-6,3</p> <p>T25</p> <p>Ø 9,7</p> <p>Ø 6,3</p> <p>L</p> <p>BS-6,1</p> <p>T25</p> <p>Ø 9,7</p> <p>Ø 6,0</p> <p>L</p> <p>75</p> |







| Combination 41A DT-4,8 / FI-P-6,8 | Combination 41B DT-S-4,8 / FI-P-6,8 |
|--|--|
| <p>FI-P-6,8</p>  <p>DT-4,8</p>  | <p>FI-P-6,8</p>  <p>DT-S-4,8</p>  |

| Combination 42A DT-6,3 / FI-P-6,8 | Combination 42B DT-S-6,3 / FI-P-6,8 |
|--|---|
| <p>FI-P-6,8</p>  <p>DT-6,3</p>  <p>DT-S-6,3</p>  | <p>FI-P-6,8</p>  <p>DT-S-6,3</p>  |

| Combination 43A LBS-T25-8,0 / FI-P-6,8 | Combination 43B LBS-S-T25-8,0 / FI-P-6,8 |
|--|---|
| <p>FI-P-6,8</p>  <p>LBS-T25-8,0</p>  <p>FI-P-6,8</p>  <p>LBS-S-T25-8,0</p>  | |




| Combination 44A TS-T25-6,0 / FI-P-6,8 | Combination 44B Sarnafast SBF-6,0 / FI-P-6,8 |
|---|--|
| <p>FI-P-6,8</p>  <p>TS-T25-6,0</p>  <p>Sarnafast SBF-6,0</p>  | <p>FI-P-6,8</p>  <p>Sarnafast SBF-6,0</p>  |

| Combination 45A Sarnafast SBF-S-6,0 / FI-P-6,8 | Combination 45B FB-S-T25-7,5 / FI-P-6,8 |
|---|---|
| <p>FI-P-6,8</p>  | <p>FI-P-6,8</p>  |
| <p>Sarnafast SBF-S-6,0</p>  <p>FB-S-T25-7,5</p>  | |




| Combination 46A BS-4,8 / FI-P-16,0 / FI-R-20 | Combination 46B BS-S-4,8 / FI-P-16,0 / FI-R-20 |
|--|---|
|   |   |
|  |  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 46</p> | |



English translation prepared by DIBt

Combination 47A
TI-T25-6,3 / FI-P-16,0 / FI-R-20







Combination 47B
BS-6,1 / FI-P-16,0 / FI-R-20







| Combination 48A DT-4,8 / FI-P-16,0 / FI-R-20 | Combination 48B DT-S-4,8 / FI-P-16,0 / FI-R-20 |
|--|---|
|  <p>FI-R-20</p> <p>FI-P-16,0</p> <p>DT-4,8</p> |  <p>FI-R-20</p> <p>FI-P-16,0</p> <p>DT-S-4,8</p> |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 48</p> |

English translation prepared by DIBt

Combination 49A
TS-T25-6,0 / FI-P-16,0 / FI-R-20










Combination 49B
Sarnafast SBF-6,0 / FI-P-16,0 / FI-R-20











English translation prepared by DIBt



| Combination 50A Sarnafast SBF-S-6,0 / FI-P-16,0 / FI-R-20 | Combination 50B TIA-T25-6,3 / FI-P-16,0 / FI-R-20 |
|--|--|
| <p>FI-R-20</p> <p>FI-P-16,0</p> | <p>FI-R-20</p> <p>FI-P-16,0</p> |
| <p>Sarnafast SBF-S-6,0</p> <p>TIA-T25-6,3</p> | |

English translation prepared by DIBt





| | |
|---|--|
| <p>Combination 51A TIA-T25-6,3 / FI-R-20 / Sarnabar</p>   | <p>Combination 51B IRF-4,8 / IRF-40x40</p>   |
|   |  |





| Combination 52A IRF-4,8 / IRF-64x64 | Combination 52B IRF-4,8 / IRF-82x40 |
|---|--|
|  |  |
|  |  |
| SFS intec flat roof fasteners | Annex 52 |





| Combination 53A IRF-4,8 / IRF-40 | Combination 53B IRFP-6,3 / IRFP-40x40 |
|---|---|
|   |   |
|  |  |
| SFS intec flat roof fasteners | Annex 53 |





| Combination 54A IRFP-6,3 / IRFP-64x64 | Combination 54B IRFP-6,3 / IRFP-82x40 |
|---|---|
|  |  |
|  |  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 54</p> | |





| Combination 55A IRFP-6,3 / IRFP-40 | Combination 55B TI-T25-6,3 / Isolfix SRT |
|--|---|
| <p>IRFP-40</p> <p>0.8</p> <p>Ø 40</p> <p>6.0</p> <p>2.0</p> <p>Ø 6.2</p> <p>IRFP-6,3</p> <p>T25</p> <p>Ø 12</p> <p>L</p> <p>50</p> <p>Ø 6.3</p> <p>TI-T25-6,3</p> <p>T25</p> <p>Ø 9.7</p> <p>L</p> <p>50</p> <p>Ø 6.3</p> | <p>Isolfix SRT</p> <p>Ø 11</p> <p>43</p> <p>76</p> <p>5.6</p> <p>TI-T25-6,3</p> <p>T25</p> <p>Ø 9.7</p> <p>L</p> <p>50</p> <p>Ø 6.3</p> |







| Combination 56A Sarnafast SBF-6,0 / Isolfix SRT | Combination 56B Sarnafast SBF-S-6,0 / Isolfix SRT |
|---|--|
|  |  |
|  |  |
| SFS intec flat roof fasteners | Annex 56 |





| Combination 57A BS-6,7 / Isolfix SRT | Combination 57B Sarnafast SBF-6,0 / Sarnafast KTL-82x40 |
|---|--|
|  |  |
|  |  |
| SFS intec flat roof fasteners | Annex 57 |

| Combination 58A Sarnafast SBF-6,0 / Sarnafast DTL-70x70 | Combination 58B Sarnafast SBF-6,0 / IF/IG-C-82x40 |
|---|---|
| <p>Sarnafast DTL-70x70</p>  | <p>IF/IG-C-82x40</p>  |
| <p>Sarnafast SBF-6,0</p>  | <p>Sarnafast SBF-6,0</p>  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 58</p> | |





| Combination 59A Sarnafast SBF-S-6,0 / Sarnafast KTL-82x40 | Combination 59B Sarnafast SBF-S-6,0 / Sarnafast DTL-70x70 |
|--|---|
| <p>Sarnafast KTL-82x40</p>  | <p>Sarnafast DTL-70x70</p>  |
| <p>Sarnafast SBF-S-6,0</p>  | <p>Sarnafast SBF-S-6,0</p>  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 59</p> | |





| Combination 60A Sarnafast SBF-S-6,0 / IF/IG-C-82x40 | Combination 60B Sarnafast SBF-S-6,0 / Sarnabar Tube SFT-50 |
|--|--|
| <p>IF/IG-C-82x40</p>  | <p>Sarnafast Tube SFT-50</p>  |
| <p>Sarnafast SBF-S-6,0</p>  | <p>Sarnafast SBF-S-6,0</p>  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 60</p> | |

| Combination 61A Sarnafast SBF-S-6,0 / Sarnabar Tube SBT-20 / Sarnabar | Combination 61B Sarnafast SBF-6,0 / SBIW-70x70 / Sarnabar Tube SBT-20 |
|---|---|
| <p>Sarnabar Tube SBT-20</p>  <p>Sarnabar</p>  | <p>Sarnabar Tube SBT-20 SBIW-70x70</p>   |
|  |  |

| Combination 62A TIF-N-6,3 / RH45 | Combination 62B TIA-T25-6,3 / R75 |
|---|---|
|  |  |
|  |  |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 62</p> | |

English translation prepared by DIBt





| Combination 63A TIA-T25-6,3 / ST-25 | Combination 63B BS-4,8 / ST-25 |
|---|--|
|  <p>ST-25</p> <p>$\varnothing 5,65$</p> <p>$\varnothing 11,0$</p> <p>$\varnothing 24,0$</p> <p>3</p> <p>L</p> <p>$\varnothing 15,1$</p> |  <p>ST-25</p> <p>$\varnothing 5,65$</p> <p>$\varnothing 11,0$</p> <p>$\varnothing 24,0$</p> <p>3</p> <p>L</p> <p>$\varnothing 15,1$</p> |
|  <p>TIA-T25-6,3</p> <p>T25</p> <p>$\varnothing 9,7$</p> <p>$\varnothing 6,9$</p> <p>22</p> <p>$\varnothing 6,3$</p> <p>L</p> |  <p>BS-4,8</p> <p>$\varnothing 8,8$</p> <p>$\varnothing 4,9$</p> <p>75</p> <p>L</p> |
| SFS intec flat roof fasteners | Annex 63 |





| Combination 64A TI-T25-6,3 / ST-25 | Combination 64B TPR-L-6,3 / IF/IG-C-82x40 |
|---|---|
| <p>ST-25</p>  | <p>IF/IG-C-82x40</p>  |
|  |  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 64</p> |

English translation prepared by DIBt

| Combination 65A LBS-S-T25-8,0 / IF/IG-C-82x40 | Combination 65B BS-4,8 / NPP |
|---|---------------------------------|
| <p>IF/IG-C-82x40</p> <p>LBS-S-T25-8,0</p> <p>BS-4,8</p> | <p>NPP</p> |





English translation prepared by DIBt

| Combination 66A BS-S-4,8 / NPP | Combination 66B BS-4,8 / NPS |
|---|--|
| <p>NPP</p>  | <p>NPS</p>  |
|  |  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 66</p> |







| Combination 67A BS-6,7 / NPS | Combination 67B BS-S-6,7 / NPS |
|---|--|
|   |   |
| SFS intec flat roof fasteners | Annex 67 |






English translation prepared by DIBt





| Combination 68A TI-T25-6,3 / NPS | Combination 68B TIA-T25-6,3 / Sarnabar Tube SBT-20 / Sarnabar |
|--------------------------------------|--|
| | |
| | |
| SFS intec flat roof fasteners | Annex 68 |






| Combination 69A IWF-5,2 / MW-40-F | Combination 69B IWF-5,2 / MW-40-R |
|--|---|
|   |   |





English translation prepared by DIBt





| Combination 70A Sarnafast SBF-6,0 / R75 | Combination 70B BS3-4,8 / RP48-3N |
|--|--|
|   |   |
|  |  |
| Sarnafast SBF-6,0 | BS3-4,8 |
| SFS intec flat roof fasteners | |
| Annex 70 | |






| Combination 71A BS-4,8 / MW-40-F | Combination 71B BS-6,1 / MW-40-F |
|--|---|
|    |   |






| Combination 72A BS-4,8 / IR-82x40 | Combination 72B BS-6,1 / IRD-82x40 |
|---|---|
| <p>IR-82x40</p>  | <p>IRD-82x40</p>  |
|  |  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 72</p> |








| Combination 73A TI-T25-6,3 / MW-40-F | Combination 73B TS-T25-6,0 / MW-40-F |
|---|--|
|    |   |




| Combination 74A TI-T25-6,3 / IRD-82x40 | Combination 74B IWF-5,2 / IR-82x40 |
|--|---|
| <p>IRD-82x40</p>  <p>TI-T25-6,3</p>  <p>IWF-5,2</p>  | <p>IR-82x40</p>  |





| Combination 75A Sarnafast SF-4,8 / Sarnabar | Combination 75B Sarnafast SBF-6,0 / Sarnabar |
|---|---|
|   |   |





| Combination 76A Sarnafast SBF-S-6,0 / Sarnabar | Combination 76B IR2-4,8 / Sarnabar |
|---|--|
|    |   |

| Combination 77A DT-4,8 / Sarnabar | Combination 77B DT-4,8 / Sarnabar Tube SBT-20 / Sarnabar |
|---|--|
|   |    |
| SFS intec flat roof fasteners | Annex 77 |

| Combination 78A DT-S-4,8 / Sarnabar | Combination 78B DT-S-4,8 / Sarnabar Tube SBT-20 / Sarnabar |
|--|--|
|    |     |





| Combination 79A DT-6,3 / Sarnabar | Combination 79B DT-S-6,3 / Sarnabar |
|---|--|
|   |   |





| Combination 80A IW-S-5,0 / Sarnabar | Combination 80B IW-T-5,0 / Sarnabar |
|---|---|
|   |   |
|  |  |
| SFS intec flat roof fasteners | Annex 80 |

| Combination 81A LBS-S-T25-8,0 / Sarnabar | Combination 81B BS-S-6,1 / FI-P-6,8 |
|---|---|
|  <p>Sarnabar</p>  <p>LBS-S-T25-8,0</p> | <p>FI-P-6,8</p>  <p>BS-S-6,1</p>  <p>BS-S-6,1</p> |





English translation prepared by DIBt





| Combination 82A BS-S-6,1 / FI-P-16,0 / FI-R-20 | Combination 82B LBS-S-T25-8,0 / IRD-82x40 |
|---|--|
| <p>FI-R-20</p> <p>FI-P-16,0</p> <p>BS-S-6,1</p> | <p>IRD-82x40</p> <p>LBS-S-T25-8,0</p> |
| | |
| | |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 82</p> | |

| Combination 83A LBS-T25-8,0 / IRD-82x40 | Combination 83B LBS-T25-8,0 / IF/IG-C-82x40 |
|--|---|
| <p>IRD-82x40</p>  | <p>IF/IG-C-82x40</p>  |
| <p>LBS-T25-8,0</p>  | <p>LBS-T25-8,0</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 83</p> |

| Combination 84A IWF-5,2 / FI-P-6,8 | Combination 84B IW-S-5,0 / FI-P-6,8 |
|---|---|
| <p>FI-P-6,8</p>  <p>IWF-5,2</p>  | <p>FI-P-6,8</p>  <p>IW-S-5,0</p>  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 84</p> |

English translation prepared by DIBt

| Combination 85A TPR-L-6,3 / FI-P-6,8 | Combination 85B DT-4,8 / ID-70x70 |
|---|---|
| <p>FI-P-6,8</p>  <p>TPR-L-6,3</p>  <p>DT-4,8</p>  | <p>ID-70x70</p>  |






| Combination 86A DT-6,3 / ID-70x70 | Combination 86B DT-4,8 / R75 |
|---|--|
| <p>ID-70x70</p>  | <p>R75</p>  |
|  |  |
| <p>SFS intec flat roof fasteners</p> | <p>Annex 86</p> |

English translation prepared by DIBt







| Combination 87A DT-S-4,8 / R75 | Combination 87B TPR-L-6,3 / IL-C-82x40 |
|---|--|
| <p>R75</p> <p>Top view: Ø 11, Ø 5,6, Ø 73.</p> <p>Side view: L, Ø 15,1.</p> <p>Cross-section: Ø 9,7, Ø 4,8.</p> | <p>IL-C-82x40</p> <p>Top view: Ø 7, 4,5.</p> <p>Side view: 82, 40.</p> |
| <p>TPR-L-6,3</p> <p>Top view: Ø 12,5.</p> <p>Side view: Ø 6,3, L.</p> | <p>DT-S-4,8</p> <p>Top view: SFS S.</p> <p>Side view: L.</p> |
| SFS intec flat roof fasteners | Annex 87 |





| Combination 88A BS-4,8 / IPF45 / FI-R-20 | Combination 88B BS-4,8 / IPF70 / FI-R-20 |
|---|---|
| <p>FI-R-20</p> <p>Top view dimensions: Ø 6,4, Ø 10,2, Ø 19,8, Ø 13, L.</p> <p>Side cross-section dimensions: Ø 6,4, Ø 10,2, Ø 13.</p> | <p>IPF45</p> <p>Top view dimension: Ø 45.</p> <p>Side cross-section dimensions: 0,80, Ø 13,2, 1,8.</p> |
| <p>BS-4,8</p> <p>Side cross-section dimensions: T25, Ø 8,8, 75, Ø 4,9, Ø 4,9, L.</p> | <p>FI-R-20</p> <p>Top view dimensions: Ø 6,4, Ø 10,2, Ø 19,8, Ø 13, L.</p> <p>Side cross-section dimensions: Ø 6,4, Ø 10,2, Ø 13.</p> |
| <p>IPF70</p> <p>Top view dimension: Ø 70.</p> <p>Side cross-section dimensions: 0,80, Ø 13,2, 2,8.</p> | <p>BS-4,8</p> <p>Side cross-section dimensions: T25, Ø 8,8, 75, Ø 4,9, Ø 4,9, L.</p> |
| <p>SFS intec flat roof fasteners</p> | |
| <p>Annex 88</p> | |

| Combination 89A BS-4,8 / Isolfast SQT | Combination 89B Sarnafast SF-4,8 / IF/IG-C-82x40 |
|--|--|
| <p>Isolfast SQT</p> <p>Dimensions: Top view - Ø 9,5, Ø 5,2; Side view - 43, 76, L, Ø 13,3.</p> | <p>IF/IG-C-82x40</p> <p>Top view dimensions: 1, Ø 7,5, 5,8. Side view dimensions: 82, 40.</p> |
| <p>BS-4,8</p> <p>Side view dimensions: T25, Ø 8,8, L, Ø 4,9.</p> | <p>Sarnafast SF-4,8</p> <p>Side view dimensions: 75, L. Cross-section dimensions: Ø 10,5, Ø 4,9, 75.</p> |
| SFS intec flat roof fasteners | Annex 89 |

| | |
|---|--|
| Combination 90A LBS-T25-8,0 / Sarnabar | Combination 90B Sarnafast SBF-6,0 / Sarnaweld disc 6,8 |
|   |   |
|  | |

| Combination 91A Sarnafast SBF-6,0 / Sarnaweld disc 16 / Sarnabar Tube SBT-20 | Combination 91B Sarnafast SBF-S-6,0 / Sarnaweld disc 6,8 |
|--|---|
| <p>Sarnabar Tube SBT-20 Sarnaweld disc 16</p> <p>Sarnaweld disc 6,8</p> | |
| <p>Sarnafast SBF-6,0</p> | |
| SFS intec flat roof fasteners | |
| Annex 91 | |

| Combination 92A Sarnafast SBF-S-6,0 / Sarnaweld disc 16 / Sarnabar Tube SBT-20 | Combination 92B IR2-S-4,8 / Sarnabar |
|---|--|
| <p>Sarnabar Tube SBT-20</p>  <p>Sarnaweld disc 16</p>  |  <p>IR2-S-4,8</p>  |
| <p>Sarnafast SBF-S-6,0</p>  |  |

| Combination 93A IR3-4,8 / Sarnabar | Combination 93B TI-6,3 / Sarnabar |
|---|---|
|   |   |
| Sarnabar | Sarnabar |
| IR3-4,8 | TI-6,3 |
| SFS intec flat roof fasteners | Annex 93 |

| Combination 94A IR2-4,8 / Sarnafast KT-82x40 | Combination 94B BSF-N-6,1 / RH45 |
|---|--|
| <p>Sarnafast KT-82x40</p> <p>The top view shows a circular base with two semi-circular flanges and a central hole labeled 'KT'. The side cross-section shows a thickness of 1 mm at the top, a shoulder diameter of Ø 5,1, and a total height of 8 mm.</p> | <p>RH45</p> <p>The top view shows a circular head with a diameter of Ø 7,2 and a thickness of 9,4 mm. The side cross-section shows a total length L, a neck diameter of Ø 45, and a base diameter of Ø 15,15.</p> |
| <p>IR2-4,8</p> <p>The side cross-section shows a total length L, a neck diameter of Ø 10,5, and a base diameter of Ø 4,9. The top view shows a head diameter of Ø 8 mm.</p> | <p>BSF-N-6,1</p> <p>The side cross-section shows a total length L, a neck diameter of Ø 6,1, and a base diameter of 9 mm. The top view shows a head diameter of Ø 9,0 mm and a thickness of 13 mm.</p> |

| | | Characteristic axial loading resistance $N_{R,k}$ [kN] for metallic substructures | | | | | | | | | | | | | | | |
|-------------|---------------------------------|---|-----------------------------|------|------|------|------|---|------|------|------|------|------|--|------|---|--|
| Combination | SFS intec flat roof fastener | Steel sheets EN 10346 $t \geq [mm]$ | | | | | | Steel sheets S350GD EN 10346 $t \geq [mm]$ | | | | | | Perforated Steel sheets S320GD EN 10346 $t \geq [mm]$ | | Aluminium sheets $R_m \geq 195 \text{ N/mm}^2$ $t \geq 0,60 \text{ mm}$ | |
| | | Fastener | Stress Plate / Sleeve / Bar | 0,50 | 0,63 | 0,70 | 0,75 | 0,80 | 0,88 | 1,00 | 1,25 | 1,50 | 0,70 | 1,00 | 0,65 | 0,75 | |
| 1A | IR2-4,8 | IR-82x40 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 3,15 | - | 1,44 | 2,27 | 1,39 | 1,74 | - | |
| 1B | IR2-4,8 | IF-70x70 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 3,15 | - | 1,44 | 2,27 | 1,39 | 1,74 | - | |
| 2A | IR2-S-4,8 | IR-82x40 | - | 0,90 | 1,13 | 1,29 | 1,43 | 1,62 | 1,97 | - | - | - | - | - | - | - | |
| 2B | IR3-4,8 | IR-82x40 | - | - | - | - | - | - | 1,26 | 2,00 | 2,63 | - | - | - | - | - | |
| 3A | IR2-C-4,8 | IRC/W-82x40 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 2,83 | - | 1,44 | 2,27 | 1,39 | 1,74 | - | |
| 3B | BS-4,8 | RP45 | - | 1,09 | 1,23 | 1,23 | 1,23 | 1,23 | 1,23 | - | 1,23 | 1,23 | 1,23 | 1,23 | - | - | |
| 4A | BS-4,8 | R45 | - | 1,09 | 1,34 | 1,38 | 1,38 | 1,38 | 1,38 | - | 1,38 | 1,38 | 1,38 | 1,38 | - | - | |
| 4B | BS-4,8 | R75 | - | 1,09 | 1,34 | 1,38 | 1,38 | 1,38 | 1,38 | - | 1,38 | 1,38 | 1,38 | 1,38 | - | - | |
| 5A | BS-4,8 | RP75 | - | 1,09 | 1,23 | 1,23 | 1,23 | 1,23 | 1,23 | - | 1,23 | 1,23 | 1,23 | 1,23 | - | - | |
| 5B | BS-4,8 | TP5 | - | 1,09 | 1,34 | 1,38 | 1,38 | 1,38 | 1,38 | - | 1,38 | 1,38 | 1,38 | 1,38 | - | - | |
| 6A | BS-4,8 | TPP | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,19 | 2,19 | - | 1,44 | 2,19 | 1,39 | 1,74 | - | |
| 6B | BS-4,8 | R48-3N | - | 1,09 | 1,34 | 1,38 | 1,38 | 1,38 | 1,38 | - | 1,38 | 1,38 | 1,38 | 1,38 | - | - | |
| 7A | BS-4,8 | RP48-3N | - | 1,09 | 1,16 | 1,16 | 1,16 | 1,16 | 1,16 | - | 1,16 | 1,16 | 1,16 | 1,16 | - | - | |
| 7B | BS-4,8 | SH-18/65 / Protan steelbar | - | 1,03 | 1,03 | 1,03 | 1,03 | 1,03 | 1,03 | - | 1,03 | 1,03 | 1,03 | 1,03 | - | - | |
| 8A | BS-S-4,8 | RP45 | - | 0,87 | 1,09 | 1,23 | 1,23 | 1,23 | 1,23 | - | - | - | - | - | - | - | |
| 8B | BS-S-4,8 | TPP | - | 0,87 | 1,09 | 1,24 | 1,38 | 1,61 | 1,96 | - | - | - | - | - | - | - | |
| 9A | BS3-4,8 | RP45 | - | - | - | - | - | - | 1,23 | 1,23 | - | - | - | - | - | - | |
| 9B | BS-6,1 | R45 | - | 1,17 | 1,38 | 1,42 | 1,42 | 1,42 | 1,42 | - | 1,42 | 1,42 | 1,42 | 1,42 | - | - | |
| 10A | IFP2-6,7 | IRP-82x40 | - | - | - | - | - | - | - | - | - | - | - | - | 0,87 | - | |
| 10B | BS-6,7 | R45 | - | - | - | - | - | - | - | - | - | - | - | - | 0,87 | - | |

¹⁾ for Steel sheets S280GD the values have to be reduced to 92%

Characteristic axial loading resistance $N_{R,k}$ [kN] for metallic substructures

| Combination | Fastener | SFS intec flat roof fastener | Steel sheets | | | | | | | | | | | | Perforated Steel sheets S320GD EN 10346 $t \geq [mm]$ | Aluminium sheets $R_m \geq 195$ N/mm ² $t \geq 0,60$ mm |
|-------------|----------------------|--------------------------------------|---|------|------|-------------------------------------|------|------|-------------------------------------|------|------|------|------|------|--|--|
| | | | S320GD ¹⁾ EN 10346 $t \geq [mm]$ | | | S350GD EN 10346 $t \geq [mm]$ | | | S420GD EN 10346 $t \geq [mm]$ | | | | | | | |
| 11A | BS-6,7 | R75 | - | - | - | - | - | - | - | - | - | - | - | - | - | 0,87 |
| 11B | BS-6,7 | TPS | - | - | - | - | - | - | - | - | - | - | - | - | - | 0,87 |
| 12A | BS-S-6,7 | R45 | - | - | - | - | - | - | - | - | - | - | - | - | - | 0,87 |
| 12B | BS-S-6,7 | R75 | - | - | - | - | - | - | - | - | - | - | - | - | - | 0,87 |
| 13A | BS-S-6,7 | TPS | - | - | - | - | - | - | - | - | - | - | - | - | - | 0,87 |
| 13B | TPR-L-6,3 | IRD-8x40 | 0,99 ²⁾ | - | - | - | - | - | - | - | - | - | - | - | - | 0,69 ²⁾ |
| 28B | BS-4,8 | Sarnafast Tube SFT-50 | - | 1,09 | 1,34 | 1,52 | 1,66 | 1,66 | 1,66 | - | 1,44 | 1,66 | 1,39 | 1,66 | - | - |
| 29A | BS-4,8 | Sarnabbar Tube SBT-20 / Sarnabbar | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,09 | 2,09 | - | 1,44 | 2,09 | 1,39 | 1,74 | - |
| 29B | BS-S-4,8 | Sarnafast Tube SFT-50 | - | 0,87 | 1,09 | 1,24 | 1,38 | 1,61 | 1,66 | - | - | - | - | - | - | - |
| 30A | BS-S-4,8 | Sarnabbar Tube SBT-20 / Sarnabbar | - | 0,87 | 1,09 | 1,24 | 1,38 | 1,61 | 1,96 | - | - | - | - | - | - | - |
| 30B | Sarnafast SF-4,8 | Sarnafast KT-82x40 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 3,15 | - | 1,44 | 2,27 | 1,39 | 1,74 | - |
| 31A | Sarnafast SF-4,8 | Sarnafast DT-70x70 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 3,15 | - | 1,44 | 2,27 | 1,39 | 1,74 | - |
| 31B | Sarnafast SBF-6,0 | Sarnafast Tube SFT-50 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,66 | 1,66 | - | 1,58 | 1,66 | 1,57 | 1,66 | - | - |
| 32A | Sarnafast SBF-6,0 | Sarnabbar Tube SBT-20 / Sarnabbar | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,10 | - | 1,58 | 2,10 | 1,57 | 1,92 | - |
| 35A | IF2-6,1 | IRD-8x40 | - | 1,11 | - | - | - | - | 1,16 | - | - | - | - | - | - | - |
| 35B | IF2-6,1 | ID-70x70 | - | 1,11 | - | - | - | 1,16 | - | - | - | - | - | - | - | - |
| 39A | BS-4,8 | Fl-P-6,8 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 2,29 | - | 1,44 | 2,27 | 1,39 | 1,74 | - |
| 39B | BS-S-4,8 | Fl-P-6,8 | - | 0,87 | 1,09 | 1,24 | 1,38 | 1,61 | 1,96 | - | - | - | - | - | - | - |
| 40B | BS-6,1 | Fl-P-6,8 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,83 | - | 1,58 | 2,19 | 1,57 | 1,92 | - |
| 44B | Sarnafast SBF-6,0 | Fl-P-6,8 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,83 | - | 1,58 | 2,19 | 1,57 | 1,92 | - |

¹⁾ for steel sheets S280GD the values have to be reduced to 92%
²⁾ predrill-diameter = 7,0 mm

Characteristic axial loading resistance $N_{R,k}$ [kN] for metallic substructures

| Combination | SFS intec flat roof fastener | Steel sheets S320GD ¹⁾ EN 10346 $t \geq [\text{mm}]$ | | | | | | | | | | | | Steel sheets S350GD EN 10346 $t \geq [\text{mm}]$ | | | Steel sheets S420GD EN 10346 $t \geq [\text{mm}]$ | | | Perforated Steel sheets S320GD EN 10346 $t \geq 0,75 \text{ mm}$ | | | Aluminium sheets $R_m \geq 195 \text{ N/mm}^2$ $t \geq 0,60 \text{ mm}$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------|---------------------------------|--|-----------------------------|------|------|------|------|------|------|------|------|------|------|--|------|------|--|-----------------------------|---------------------|---|------|------|---|------|------|------|------|------|------|------|------|----------|-----------------------------|------|------|----------|---------------------|------|------|------|------|------|------|------|------|------|----------|-----------------------------|------|------|------|------|--------|---------------------|------|------|------|------|------|------|------|----------|-----------------------------|------|------|------|------|------|------|------|---------------------|---------------------|------|------|------|------|------|------|------|------|---|------|------|------|------|---|---|-----|---------------------|---------------------|---|------|------|------|------|------|------|---|---|---|---|---|---|---|-----|---------|-----------|---|---|------|------|------|------|---|---|---|---|---|---|---|---|-----|---------|-----------|---|---|------|------|------|------|---|---|---|---|---|---|---|---|-----|---------|-----------|---|---|------|------|------|------|---|---|---|---|---|---|---|---|-----|---------|--------|---|---|------|------|------|------|---|---|---|---|---|---|---|---|-----|----------|------------|---|---|---|---|---|---|---|---|---|---|---|---|---|-----|----------|------------|---|---|---|---|---|---|---|---|---|---|---|---|---|-----|----------|------------|---|---|---|---|---|---|---|---|---|---|---|---|---|-----|----------|---------|---|---|---|---|---|---|---|---|---|---|---|---|---|-----|---------------------|-------------|---|------|------|------|------|------|------|---|------|------|------|------|---|---|-----|---------------------|-------------|---|------|------|------|------|------|------|---|---|---|---|---|---|---|-----|--------|-------------|---|---|---|---|---|---|---|---|---|---|---|---|---|-----|-------------------|---------------------|---|------|------|------|------|------|------|------|---|------|------|------|------|---|---|-----|-------------------|---------------------|---|------|------|------|------|------|------|------|---|------|------|------|------|---|---|-----|-------------------|--------------|---|------|------|------|------|------|------|------|---|------|------|------|------|---|---|
| | | Fastener | Stress Plate / Sleeve / Bar | 0,50 | 0,63 | 0,70 | 0,75 | 0,80 | 0,88 | 1,00 | 1,25 | 1,50 | 0,70 | 1,00 | 0,65 | 0,75 | Fastener | Stress Plate / Sleeve / Bar | 0,50 | 0,63 | 0,70 | 0,75 | 0,80 | 0,88 | 1,00 | 1,25 | 1,50 | 0,70 | 1,00 | 0,65 | 0,75 | Fastener | Stress Plate / Sleeve / Bar | 0,50 | 0,63 | 0,70 | 0,75 | 0,80 | 0,88 | 1,00 | 1,25 | 1,50 | 0,70 | 1,00 | 0,65 | 0,75 | Fastener | Stress Plate / Sleeve / Bar | 0,50 | 0,63 | 0,70 | 0,75 | 0,80 | 0,88 | 1,00 | 1,25 | 1,50 | 0,70 | 1,00 | 0,65 | 0,75 | Fastener | Stress Plate / Sleeve / Bar | 0,50 | 0,63 | 0,70 | 0,75 | 0,80 | 0,88 | 1,00 | 1,25 | 1,50 | 0,70 | 1,00 | 0,65 | 0,75 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 45A | Sarnafast SBF-S-6,0 | Fl-P-6,8 | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,39 | - | - | - | - | - | - | - | 46A | BS-4,8 | Fl-P-16,0 / Fl-R-20 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,21 | - | 1,44 | 2,21 | 1,39 | 1,74 | - | - | - | 46B | BS-S-4,8 | Fl-P-16,0 / Fl-R-20 | - | 0,87 | 1,09 | 1,24 | 1,38 | 1,61 | 1,96 | - | - | - | - | - | - | - | 47B | BS-6,1 | Fl-P-16,0 / Fl-R-20 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,17 | - | 1,58 | 2,17 | 1,57 | 1,92 | - | - | 49B | Sarnafast SBF-S-6,0 | Fl-P-16,0 / Fl-R-20 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,17 | - | 1,58 | 2,17 | 1,57 | 1,92 | - | - | 50A | Sarnafast SBF-S-6,0 | Fl-P-16,0 / Fl-R-20 | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,17 | - | - | - | - | - | - | - | 51B | IRF-4,8 | IRF-40x40 | - | - | 1,30 | 1,31 | 1,33 | 1,35 | - | - | - | - | - | - | - | - | 52A | IRF-4,8 | IRF-64x64 | - | - | 1,30 | 1,31 | 1,33 | 1,35 | - | - | - | - | - | - | - | - | 52B | IRF-4,8 | IRF-82x40 | - | - | 1,30 | 1,31 | 1,33 | 1,35 | - | - | - | - | - | - | - | - | 53A | IRF-4,8 | IRF-40 | - | - | 1,30 | 1,31 | 1,33 | 1,35 | - | - | - | - | - | - | - | - | 53B | IRFP-6,3 | IRFP-40x40 | - | - | - | - | - | - | - | - | - | - | - | - | - | 54A | IRFP-6,3 | IRFP-64x64 | - | - | - | - | - | - | - | - | - | - | - | - | - | 54B | IRFP-6,3 | IRFP-82x40 | - | - | - | - | - | - | - | - | - | - | - | - | - | 55A | IRFP-6,3 | IRFP-40 | - | - | - | - | - | - | - | - | - | - | - | - | - | 56A | Sarnafast SBF-S-6,0 | Isolfix SRT | - | 1,17 | 1,38 | 1,42 | 1,42 | 1,42 | 1,42 | - | 1,42 | 1,42 | 1,42 | 1,42 | - | - | 56B | Sarnafast SBF-S-6,0 | Isolfix SRT | - | 1,21 | 1,42 | 1,42 | 1,42 | 1,42 | 1,42 | - | - | - | - | - | - | - | 57A | BS-6,7 | Isolfix SRT | - | - | - | - | - | - | - | - | - | - | - | - | - | 57B | Sarnafast SBF-6,0 | Sarnafast KTL-82x40 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,56 | - | 1,58 | 2,19 | 1,57 | 1,92 | - | - | 58A | Sarnafast SBF-6,0 | Sarnafast DTL-70x70 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,56 | - | 1,58 | 2,19 | 1,57 | 1,92 | - | - | 58B | Sarnafast SBF-6,0 | IF/G-C-82x40 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,68 | - | 1,58 | 2,19 | 1,57 | 1,92 | - | - |

¹⁾ for steel sheets S280GD the values have to be reduced to 92%

²⁾ triangular array of holes, hole diameter 5,0 mm, distance of holes 12,5 mm

| Combination | SFS intec flat roof of fastener | Characteristic axial loading resistance $N_{R,k}$ [kN] for metallic substructures | | | | | | | | | | | | | |
|-------------|------------------------------------|---|-----------------------------|-------------------------------------|------|---|------|-------------------------------------|------|--|------|------|------|---|------|
| | | Steel sheets EN 10346 $t \geq [mm]$ | | | | Steel sheets EN 10346 $t \geq [mm]$ | | | | Perforated Steel sheets S320GD EN 10346 $t \geq [mm]$ | | | | Aluminium sheets $R_m \geq 195 \text{ N/mm}^2$ $t \geq 0,60 \text{ mm}$ | |
| | | S320GD ¹⁾ | | S350GD EN 10346 $t \geq [mm]$ | | S420GD EN 10346 $t \geq [mm]$ | | S420GD EN 10346 $t \geq [mm]$ | | S320GD EN 10346 $t \geq [mm]$ | | | | | |
| 59A | Sarnafast SBF-S-6,0 | Fastener | Stress Plate / Sleeve / Bar | 0,50 | 0,63 | 0,70 | 0,75 | 0,80 | 0,88 | 1,00 | 1,25 | 1,50 | 0,70 | 0,65 | 0,75 |
| 59B | Sarnafast SBF-S-6,0 | Sarnafast KTL-82x40 | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,39 | - | - | - | - | - | - |
| 60A | Sarnafast SBF-S-6,0 | Sarnafast DTL-70x70 | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,39 | - | - | - | - | - | - |
| 60B | Sarnafast SBF-S-6,0 | IF/IG-C-82x40 | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,39 | - | - | - | - | - | - |
| 61A | Sarnafast SBF-S-6,0 | Sarnafast Tube SFT-50 | - | 1,21 | 1,47 | 1,66 | 1,66 | 1,66 | 1,66 | - | - | - | - | - | - |
| 61B | Sarnafast SBF-6,0 | Sarnafast Tube SBT-20 / Sarnabar Tube SBT-20 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,10 | - | - | - | - | - |
| 63B | BS-4,8 | ST-25 | - | 1,09 | 1,34 | 1,38 | 1,38 | 1,38 | 1,38 | - | 1,38 | 1,38 | 1,38 | 1,38 | - |
| 64B | TPRL-6,3 | IF/IG-C-82x40 | 0,99 ³⁾ | - | - | - | - | - | - | - | - | - | - | 0,69 ³⁾ | |
| 65B | BS-4,8 | NPP | - | 1,09 | 1,34 | 1,45 | 1,45 | 1,45 | 1,45 | - | 1,44 | 1,45 | 1,45 | - | - |
| 66A | BS-S-4,8 | NPP | - | 0,87 | 1,09 | 1,24 | 1,38 | 1,45 | 1,45 | - | - | - | - | - | - |
| 66B | BS-4,8 | NPS | - | 1,09 | 1,34 | 1,38 | 1,38 | 1,38 | 1,38 | - | 1,38 | 1,38 | 1,38 | - | - |
| 67A | BS-6,7 | NPS | - | - | - | - | - | - | - | - | - | - | - | 0,87 ²⁾ | |
| 67B | BS-S-6,7 | NPS | - | - | - | - | - | - | - | - | - | - | - | 0,87 ²⁾ | |
| 70A | Sarnafast SBF-6,0 | R75 | - | 1,17 | 1,38 | 1,42 | 1,42 | 1,42 | 1,42 | - | 1,42 | 1,42 | 1,42 | - | - |
| 70B | BS3-4,8 | RP48-3N | - | - | - | - | - | - | 1,16 | 1,16 | - | - | - | - | - |
| 71A | BS-4,8 | MW-40-F | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 2,60 | - | 1,44 | 2,27 | 1,39 | 1,74 |
| 71B | BS-6,1 | MW-40-F | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,91 | - | 1,58 | 2,19 | 1,57 | 1,92 |
| 72A | BS-4,8 | IR-82x40 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 3,15 | - | 1,44 | 2,27 | 1,39 | 1,74 |
| 72B | BS-6,1 | IRD-82x40 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,56 | - | 1,58 | 2,19 | 1,57 | 1,92 |
| 75A | Sarnafast SF-4,8 | Sarnabar | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 3,15 | - | 1,44 | 2,27 | 1,39 | 1,74 |

¹⁾ for steel sheets S280GD the values have to be reduced to 92%

²⁾ triangular array of holes, hole diameter 5,0 mm, distance of holes 12,5 mm

³⁾ predrill-diameter = 7,0 mm

| Combination | | Characteristic axial loading resistance $N_{R,k}$ [kN] for metallic substructures | | | | | | | | | | | | | |
|---------------------------------|---|---|------|------|------|------|------|---|------|------|------|------|------|---|---|
| SFS intec flat roof fastener | | Steel sheets S320GD ¹⁾ EN 10346 $t \geq [mm]$ | | | | | | Steel sheets S350GD EN 10346 $t \geq [mm]$ | | | | | | Aluminium sheets $R_m \geq 195\text{ N/mm}^2$ $t \geq 0,60\text{ mm}$ | |
| Fastener | Stress Plate / Sleeve / Bar | 0,50 | 0,63 | 0,70 | 0,75 | 0,80 | 0,88 | 1,00 | 1,25 | 1,50 | 0,70 | 1,00 | 0,65 | 0,75 | |
| 75B Sarnafast SBF-6,0 | Sarnabar | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,91 | - | 1,58 | 2,19 | 1,57 | 1,92 | - |
| 76A Sarnafast SBF-S-6,0 | Sarnabar | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,39 | - | - | - | - | - | - | - |
| 76B IR2-4,8 | Sarnabar | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 3,15 | - | 1,44 | 2,27 | 1,39 | 1,74 | - |
| 81B BS-5-6,1 | Fl-P-6,8 | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,39 | - | - | - | - | - | - | - |
| 82A BS-5-6,1 | Fl-P-16,0 / Fl-R-20 | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,17 | - | - | - | - | - | - | - |
| 85A TPR-L-6,3 | Fl-P-6,8 | 0,99 ²⁾ | - | - | - | - | - | - | - | - | - | - | - | 0,69 ²⁾ | - |
| 87B TPR-L-6,3 | Il-C-82x40 | 0,99 ²⁾ | - | - | - | - | - | - | - | - | - | - | - | 0,69 ²⁾ | - |
| 88A BS-4,8 | IPF45 / Fl-R-20 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,21 | 2,21 | - | 1,44 | 2,21 | 1,39 | 1,74 | - |
| 88B BS-4,8 | IPF45 / Fl-R-20 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,21 | 2,21 | - | 1,44 | 2,21 | 1,39 | 1,74 | - |
| 89A BS-4,8 | Isoftfast SQT | - | 1,09 | 1,34 | 1,45 | 1,45 | 1,45 | 1,45 | 1,45 | - | 1,44 | 1,45 | 1,39 | 1,45 | - |
| 89B Sarnafast SF-4,8 | IF/G-C-82x40 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 3,15 | - | 1,44 | 2,27 | 1,39 | 1,74 | - |
| 90B Sarnafast SBF-6,0 | Sarnaweld disc 6,8 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,83 | - | 1,58 | 2,17 | 1,57 | 1,92 | - |
| 91A Sarnafast SBF-S-6,0 | Sarnaweld disc 16 / Sarnabar Tube SBT-20 | - | 1,17 | 1,38 | 1,53 | 1,63 | 1,80 | 2,04 | 2,17 | - | 1,58 | 2,17 | 1,57 | 1,92 | - |
| 91B Sarnafast SBF-S-6,0 | Sarnabar disc 6,8 | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,39 | - | - | - | - | - | - | - |
| 92A Sarnafast SBF-S-6,0 | Sarnaweld disc 16 / Sarnabar Tube SBT-20 | - | 1,21 | 1,47 | 1,66 | 1,81 | 2,04 | 2,17 | - | - | - | - | - | - | - |
| 92B IR2-S-4,8 | Sarnabar | - | 0,90 | 1,13 | 1,29 | 1,43 | 1,62 | 1,97 | - | - | - | - | - | - | - |
| 93A IR3-4,8 | Sarnabar | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 94A IR2-4,8 | Sarnafast KT-82x40 | - | 1,09 | 1,34 | 1,52 | 1,67 | 1,91 | 2,27 | 3,15 | - | 1,44 | 2,27 | 1,39 | 1,74 | - |
| 94B BSF-N-6,1 | RH45 | - | 1,17 | 1,38 | 1,53 | 1,54 | 1,54 | 1,54 | 1,54 | - | 1,54 | 1,54 | 1,54 | 1,54 | - |

¹⁾ for Steel sheets S280GD the values have to be reduced to 92%

²⁾ predrill-diameter = 7,0 mm

| Combination | SFS intec flat roof fastener | Characteristic axial loading resistance N_{Rk} [kN] for non-metallic substructures | | | | | | | | | | | |
|-------------|---------------------------------|--|--|--|----------------------|--------|---------------------------------|--------------------------------|-------|-------|---------------------------------|--------------|---------------------------------|
| | | Timber | | | Concrete EN 206-1 | | | Aerated Concrete DIN 4223-1 | | | Pumice Panel EN 1520 | | |
| | | OSB3 EN 300 $t \geq 18 \text{ mm}^1)$ | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}^2)$ | Plywood EN 636 $t \geq 18 \text{ mm}^3)$ | C12/15 | C25/30 | setting depth \geq [mm] | pre-drill diameter [mm] | P 3,3 | P 4,4 | setting depth \geq [mm] | LAC 6, D 1,0 | setting depth \geq [mm] |
| 1A | IR2-4,8 | IR-82x40 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - |
| 1B | IR2-4,8 | IF-70x70 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - |
| 2A | IR2-5-4,8 | IR-82x40 | 1,28 | 1,74 | 1,94 | - | - | - | - | - | - | - | - |
| 3A | IR2-C-4,8 | IRC/W-82x40 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - |
| 3B | BS-4,8 | RP45 | 1,23 | 1,23 | - | - | - | - | - | - | - | - | - |
| 4A | BS-4,8 | R45 | 1,38 | 1,32 | 1,38 | - | - | - | - | - | - | - | - |
| 4B | BS-4,8 | R75 | 1,38 | 1,32 | 1,38 | - | - | - | - | - | - | - | - |
| 5A | BS-4,8 | RP75 | 1,23 | 1,23 | 1,23 | - | - | - | - | - | - | - | - |
| 5B | BS-4,8 | TPS | 1,38 | 1,32 | 1,38 | - | - | - | - | - | - | - | - |
| 6A | BS-4,8 | TPP | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - |
| 6B | BS-4,8 | R48-3N | 1,38 | 1,32 | 1,38 | - | - | - | - | - | - | - | - |
| 7A | BS-4,8 | RP48-3N | 1,16 | 1,16 | 1,16 | - | - | - | - | - | - | - | - |
| 7B | BS-4,8 | SH-18/65 / Protan stielbar | 1,03 | 1,03 | 1,03 | - | - | - | - | - | - | - | - |
| 8A | BS-5-4,8 | RP45 | 1,23 | 1,23 | 1,23 | - | - | - | - | - | - | - | - |
| 8B | BS-5-4,8 | TPP | 1,28 | 1,74 | 1,96 | - | - | - | - | - | - | - | - |
| 9B | BS-6,1 | R45 | 1,32 | 1,42 | 0,72 | 1,42 | 32 | 5,0 | 0,35 | 0,58 | 75 | - | - |
| 14A | IG-6,0 | IRD-82x40 | 1,31 | 1,43 | 2,49 | - | - | - | - | - | - | - | - |
| 14B | T5-T25-6,0 | R45 | 1,31 | 1,42 | 0,44 | 0,89 | 32 | 5,0 | 1,07 | 1,42 | 75 | - | - |
| 15A | IWF-5,2 | MW-40-FH | 1,35 | 1,74 | 1,74 | - | - | - | - | - | - | - | - |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$

²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$

³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$; minimum density = 400 kg/m³

| SFS intec flat roof fastener | | Characteristic axial loading resistance N_{Rx} [kN] for non-metallic substructures | | | | | | | | | |
|---------------------------------|---------------|--|---|---|--------|--------|---------------------------------|-------------------------------|-------|---------------------------------|------------------|
| Combination | Fastener | Timber | | Concrete EN 206-1 | | | Aerated Concrete DIN 4223-1 | | | Pumice Panel EN 1520 | |
| | | OSB3 EN 300 $t \geq 18 \text{ mm}$ ¹⁾ | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}$ ²⁾ | Plywood EN 636 $t \geq 18 \text{ mm}$ ³⁾ | C12/15 | C25/30 | setting depth \geq [mm] | pre-drill diameter [mm] | P 4,4 | setting depth \geq [mm] | IAC 6, D 1,0 |
| 15B | IW-T-5,0 | IRC/W-82x40 | 1,08 | 1,12 | 2,12 | - | - | - | - | - | - |
| 16A | IW-S-5,0 | IRC/W-82x40 | 1,08 | 1,12 | 2,04 | - | - | - | - | - | - |
| 16B | LBS-S-T25-8,0 | R45 | - | - | - | - | - | - | 0,93 | 1,43 | 60 |
| 17A | LBS-T25-8,0 | MW-40-LBS | - | - | - | - | - | - | 0,93 | 1,44 | 60 |
| 17B | LBS-T25-8,0 | R45 | - | - | - | - | - | - | 0,93 | 1,43 | 60 |
| 18A | LB45 | - | - | - | - | - | - | - | 1,44 | 1,44 | 65 ⁴⁾ |
| 18B | FB-S-T25-7,5 | R45 | - | - | - | - | - | - | - | - | - |
| 19A | DT-4,8 | IRD-82x40 | - | - | 2,40 | 2,56 | 25 | 4,8 | - | - | - |
| 19B | DT-4,8 | IF/G-C-82x40 | - | - | 2,40 | 2,68 | 25 | 4,8 | - | - | - |
| 20A | DT-4,8 | IW-82x40 | - | - | 2,40 | 3,34 | 25 | 4,8 | - | - | - |
| 20B | DT-4,8 | R45 | - | - | 1,39 | 1,39 | 25 | 4,8 | - | - | - |
| 21A | DT-S-4,8 | IRD-82x40 | - | - | 2,56 | 2,56 | 25 | 4,8 | - | - | - |
| 21B | DT-S-4,8 | IF/G-C-82x40 | - | - | 2,65 | 2,68 | 25 | 4,8 | - | - | - |
| 22A | DT-S-4,8 | R45 | - | - | 1,39 | 1,39 | 25 | 4,8 | - | - | - |
| 22B | DT-6,3 | IRD-82x40 | - | - | 2,93 | 3,68 | 32 | 6,3 | - | - | - |
| 23A | DT-6,3 | IF/G-C-82x40 | - | - | 2,93 | 4,07 | 32 | 6,3 | - | - | - |
| 23B | DT-S-6,3 | IRD-82x40 | - | - | 2,23 | 3,10 | 32 | 6,3 | - | - | - |
| 24A | DT-S-6,3 | IF/G-C-82x40 | - | - | 2,23 | 3,10 | 32 | 6,3 | - | - | - |
| 24B | T1-6,3 | IRD-82x40 | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - | - |
| | | | | | 2,56 | 2,56 | 30 | | | | |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$

²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$

³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$; minimum density = 400 kg/m³

⁴⁾ pre-drill diameter = 15 mm

| Combination | | Characteristic axial loading resistance $N_{R,k}$ [kN] for non-metallic substructures | | | | | | | | | | |
|---------------------------------|-----------------------------|---|--|--|----------------------|--------|-------|--------------------------------|---------------------------------|--------------|---------------------------------|-------------------------------|
| SFS intec flat roof fastener | | Timber | | | Concrete EN 206-1 | | | Aerated Concrete DIN 4223-1 | | | Pumice Panel EN 1520 | |
| Fastener | Stress Plate / Sleeve / Bar | OSB3 EN 300 $t \geq 18 \text{ mm}^1)$ | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}^2)$ | Plywood EN 636 $t \geq 18 \text{ mm}^3)$ | C12/15 | C25/30 | P 3,3 | P 4,4 | setting depth \geq [mm] | LAC 6, D 1,0 | setting depth \geq [mm] | pre-drill diameter [mm] |
| 25A | T1-6,3 | IF/I-G-C-82x40 | - | - | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - |
| 25B | T1-6,3 | ID-70x70 | - | - | - | - | 2,73 | 3,79 | 30 | 5,0 | - | - |
| 26A | T1-T25-6,3 | R75 | - | - | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - |
| 26B | T1-T25-6,3 | TPS | - | - | - | - | 1,42 | 1,42 | 20 | 5,0 | - | - |
| 27A | T1-T25-6,3 | R48-3N | - | - | - | - | 1,42 | 1,42 | 30 | 5,0 | - | - |
| 27B | T1-T25-6,3 | R45 | - | - | - | - | 1,42 | 1,42 | 20 | 5,0 | - | - |
| 28A | T1A-T25-6,3 | R45 | - | - | - | - | 1,42 | 1,42 | 30 | 5,0 | - | - |
| 28B | BS-4,8 | Sarmafast Tube SFT-50 | 1,45 | 1,32 | 1,66 | - | - | - | - | - | - | - |
| 29A | BS-4,8 | Sarmafast Tube SBT-20 / Sarmabar | 1,45 | 1,32 | 2,09 | - | - | - | - | - | - | - |
| 29B | BS-5-4,8 | Sarmafast Tube SFT-50 | 1,28 | 1,66 | - | - | - | - | - | - | - | - |
| 30A | BS-5-4,8 | Sarmafast Tube SBT-20 / Sarmabar | 1,28 | 1,74 | 1,96 | - | - | - | - | - | - | - |
| 30B | Sarmafast SF-4,8 | Sarmafast KT-82x40 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - |
| 31A | Sarmafast SF-4,8 | Sarmafast DT-70x70 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - |
| 31B | Sarmafast SGB-6,0 | Sarmafast Tube SFT-50 | 1,32 | 1,66 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 | 75 | - |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$

²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$

³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$; minimum density = 400 kg/m³

| SFS intec flat roof fastener | | Characteristic axial loading resistance $N_{R,k}$ [kN] for non-metallic substructures | | | | | | | | | |
|---------------------------------|--------------|---|---|---|----------------------|--------|---------------------------------|--------------------------------|-------|---------------------------------|-------------------------|
| Combination | Fastener | Timber | | | Concrete EN 206-1 | | | Aerated Concrete DIN 4223-1 | | | Pumice Panel EN 1520 |
| | | OSB3 EN 300 $t \geq 18 \text{ mm}$ ¹⁾ | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}$ ²⁾ | Plywood EN 636 $t \geq 18 \text{ mm}$ ³⁾ | C12/15 | C25/30 | setting depth \geq [mm] | P 3,3 | P 4,4 | setting depth \geq [mm] | |
| 32A | TI-6,0 | Sarnafast SBF-S Sarnabar | 1,32 | 2,10 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 | 75 |
| 32B | TI-6,3 | Sarnafast DTL-70x70 | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - | - |
| 33A | TI-T25-6,3 | Sarnafast Tube SFT-50 | - | - | 2,56 | 2,56 | 30 | - | - | - | - |
| 33B | TI-T25-6,3 | Sarnafast Tube SBT-20 / Sarnabar | - | - | 1,66 | 1,66 | 20 | 5,0 | - | - | - |
| 34A | TI-S-T10-6,3 | R45 | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - | - |
| 34B | TI-S-T10-6,3 | R75 | - | - | 2,10 | 2,10 | 30 | - | - | - | - |
| 35A | IF2-6,1 | IRD-8x2x40 | 1,07 | 2,04 | 0,53 | 1,05 | 32 | 5,0 | - | - | - |
| 35B | IF2-6,1 | ID-70x70 | 1,07 | 2,04 | 0,53 | 1,05 | 32 | 5,0 | - | - | - |
| 36A | FB-S-T25-7,5 | IRD-8x2x40 | - | - | 2,40 | 1,56 | 32 | 5,0 | 1,27 | 2,11 | 75 |
| 36B | FB-S-T25-7,5 | IF/IG-C-8x2x40 | - | - | - | 3,12 | 32 | 5,0 | 1,27 | 2,11 | 75 |
| 37A | FB-S-T25-7,5 | R75 | - | - | - | - | - | - | - | 0,59 | 50 |
| 37B | IW-S-5,0 | IW-8x2x40 | 1,08 | 1,12 | 2,04 | - | - | - | - | 0,59 | 50 |
| 38A | IW-T-5,0 | IW-8x2x40 | 1,08 | 1,12 | 2,12 | - | - | - | - | 0,59 | 50 |
| 38B | IWF-5,2 | IWF-8x2x40 | 1,35 | 1,94 | 2,20 | - | - | - | - | 0,59 | 50 |
| 39A | BS-4,8 | FI-P-6,8 | 1,45 | 1,32 | 2,18 | - | - | - | - | 0,59 | 50 |
| 39B | BS-S-4,8 | FI-P-6,8 | 1,28 | 1,74 | 1,96 | - | - | - | - | 0,59 | 50 |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$
²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$
³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$; minimum density = 400 kg/m³

| Combination | | Characteristic axial loading resistance $N_{R,k}$ [kN] for non-metallic substructures | | | | | | | | | | | |
|---------------------------------|-----------------------------|---|---|---|------------------|---------------------------------|-------------------------------|-------|-------|---------------------------------|--------------|---------------------------------|-------------------------------|
| SFS intec flat roof fastener | | Timber | | | | | Concrete EN 206-1 | | | Aerated Concrete DIN 4223-1 | | Pumice Panel EN 1520 | |
| Fastener | Stress Plate / Sleeve / Bar | OSB3 EN 300 $t \geq 18 \text{ mm}$ ¹⁾ | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}$ ²⁾ | Plywood EN 636 $t \geq 18 \text{ mm}$ ³⁾ | C12/15 C25/30 | setting depth \geq [mm] | pre-drill diameter [mm] | P 3,3 | P 4,4 | setting depth \geq [mm] | LAC 6, D 1,0 | setting depth \geq [mm] | pre-drill diameter [mm] |
| 40A | TI-T25-6,3 | Fl-P-6,8 | - | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - | - | - |
| 40B | BS-6,1 | Fl-P-6,8 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 | 75 | - |
| 41A | DT-4,8 | Fl-P-6,8 | - | - | - | 2,40 | 2,83 | 25 | 4,8 | - | - | - | - |
| 41B | DT-S-4,8 | Fl-P-6,8 | - | - | - | 2,65 | 2,83 | 25 | 4,8 | - | - | - | - |
| 42A | DT-6,3 | Fl-P-6,8 | - | - | - | 2,93 | 3,82 | 32 | 6,3 | - | - | - | - |
| 42B | DT-S-6,3 | Fl-P-6,8 | - | - | - | 2,23 | 3,10 | 32 | 6,3 | - | - | - | - |
| 43A | LBS-T25-8,0 | Fl-P-6,8 | - | - | - | - | - | - | - | 0,93 | 1,44 | 60 | - |
| 43B | LBS-S-T25-8,0 | Fl-P-6,8 | - | - | - | - | - | - | - | 0,93 | 1,44 | 60 | - |
| 44A | TS-T25-6,0 | Fl-P-6,8 | 1,31 | 1,43 | 2,30 | 0,44 | 0,89 | 32 | 5,0 | 1,07 | 1,78 | 75 | - |
| 44B | Sarnafast SBF-6,0 | Fl-P-6,8 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 | 75 | - |
| 45A | Sarnafast SBF-S-6,0 | Fl-P-6,8 | 1,25 | 2,02 | 2,22 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 | 75 | - |
| 45B | FB-S-T25-7,5 | Fl-P-6,8 | - | - | - | - | - | - | - | - | - | 0,59 | 50 |
| 46A | BS-4,8 | Fl-P-16,0 / Fl-R-20 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - |
| 46B | BS-S-4,8 | Fl-P-16,0 / Fl-R-20 | 1,28 | 1,74 | 1,96 | - | - | - | - | - | - | - | - |
| 47A | TI-T25-6,3 | Fl-P-16,0 / Fl-R-20 | - | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - | - | - |
| 47B | BS-6,1 | Fl-P-16,0 / Fl-R-20 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 | 75 | - |
| 48A | DT-4,8 | Fl-P-16,0 / Fl-R-20 | - | - | - | 2,17 | 2,17 | 25 | 4,8 | - | - | - | - |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$

²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$

³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}; \text{minimum density} = 400 \text{ kg/m}^3$

| Combination | SFS intec flat roof fastener | Characteristic axial loading resistance $N_{R,k}$ [kN] for non-metallic substructures | | | | | | | | | |
|-------------|---------------------------------|---|---|---|----------------------|--------|---------------------------------|--------------------------------|-------|---------------------------------|---|
| | | Timber | | | Concrete EN 206-1 | | | Aerated Concrete DIN 4223-1 | | | Pumice Panel EN 1520 |
| | | OSB3 EN 300 | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}^2$ | Plywood EN 636 $t \geq 18 \text{ mm}^3$ ³⁾ | C12/15 | C25/30 | setting depth \geq [mm] | P 3,3 | P 4,4 | setting depth \geq [mm] | LAC 6, D 1,0 setting depth \geq [mm] |
| 48B | DT-S-4,8 | Fl-P-16,0 / Fl-R-20 | - | - | - | 2,17 | 2,17 | 4,8 | - | - | - |
| 49A | TS-T25-6,0 | Fl-P-16,0 / Fl-R-20 | 1,31 | 1,43 | 2,17 | 0,44 | 0,89 | 32 | 5,0 | 1,07 | 75 |
| 49B | Sarnafast SBF-6,0 | Fl-P-16,0 / Fl-R-20 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 |
| 50A | Sarnafast SBF-6,0 | Fl-P-16,0 / Fl-R-20 | 1,25 | 2,02 | 2,17 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 |
| 50B | TIA-T25-6,3 | Fl-P-16,0 / Fl-R-20 | - | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - |
| 51A | TIA-T25-6,3 | Fl-R-20 / Sarnabar | - | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - |
| 55B | TI-T25-6,3 | Isoftfix SRT | - | - | - | 1,42 | 1,42 | 20 | 5,0 | - | - |
| 56A | Sarnafast SBF-6,0 | Isoftfix SRT | 1,32 | 1,42 | 1,42 | 0,72 | 1,42 | 32 | 5,0 | 0,35 | 0,58 |
| 56B | Sarnafast SBF-S-6,0 | Isoftfix SRT | 1,25 | 1,42 | 1,42 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 |
| 57B | Sarnafast SBF-6,0 | Sarnafast KTL-82x40 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 |
| 58A | Sarnafast SBF-6,0 | Sarnafast DTL-70x70 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 |
| 58B | Sarnafast SBF-6,0 | IF/IG-C-82x40 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 |
| 59A | Sarnafast SBF-S-6,0 | Sarnafast KTL-82x40 | 1,25 | 2,02 | 2,22 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 |
| 59B | Sarnafast SBF-S-6,0 | Sarnafast DTL-70x70 | 1,25 | 2,02 | 2,22 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 |
| 60A | Sarnafast SBF-S-6,0 | IF/IG-C-82x40 | 1,25 | 2,02 | 2,22 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 |
| 60B | Sarnafast SBF-S-6,0 | Sarnabar Tube SFT-50 | 1,25 | 1,66 | 1,66 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 |
| 61A | Sarnafast SBF-6,0 | Sarnabar Tube SBT-20 / Sarnabar | 1,25 | 2,02 | 2,10 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 |
| 61B | Sarnafast SBF-6,0 | SBIW-70x70 / Sarnabar Tube SBT-20 | 1,32 | 2,10 | 2,10 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$
²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$
³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$; minimum density = 400 kg/m³

| SFS intec flat roof fastener | | Characteristic axial loading resistance $N_{R,k}$ [kN] for non-metallic substructures | | | | | | | | | |
|---------------------------------|----------------------|---|---|---|----------------------|--------|---------------------------------|--------------------------------|-------|---------------------------------|-------------------------|
| Combination | Fastener | Timber | | | Concrete EN 206-1 | | | Aerated Concrete DIN 4233-1 | | | Pumice Panel EN 1520 |
| | | OSB3 EN 300 | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}^2$ | Plywood EN 636 $t \geq 18 \text{ mm}^3$ | C12/15 | C25/30 | setting depth \geq [mm] | P 3,3 | P 4,4 | setting depth \geq [mm] | |
| 62A | TF-N-6,3 | RH45 | - | - | - | 1,54 | 1,54 | 20 | 5,0 | - | - |
| 62B | TIA-T25-6,3 | R75 | - | - | - | 1,42 | 1,42 | 20 | 5,0 | - | - |
| 63A | TIA-T25-6,3 | ST-25 | - | - | - | 1,42 | 1,42 | 20 | 5,0 | - | - |
| 63B | BS-4,8 | ST-25 | 1,38 | 1,32 | 1,38 | - | - | - | - | - | - |
| 64A | TI-T25-6,3 | ST-25 | - | - | - | 1,42 | 1,42 | 20 | 5,0 | - | - |
| 65A | LBS-S-T25-8,0 | IF/IG-C-82x40 | - | - | - | 1,42 | 1,42 | 30 | - | - | - |
| 65B | BS-4,8 | NPP | 1,45 | 1,32 | 1,45 | - | - | - | - | - | - |
| 66A | BS-S-4,8 | NPP | 1,28 | 1,45 | 1,45 | - | - | - | - | - | - |
| 66B | BS-4,8 | NPS | 1,38 | 1,32 | 1,38 | - | - | - | - | - | - |
| 68A | TI-T25-6,3 | NPS | - | - | - | 1,42 | 1,42 | 20 | 5,0 | - | - |
| 68B | TIA-T25-6,3 | Sarnabar Tube SBT-20 / Sarnabar | - | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - |
| 69A | IWF-5,2 | MW-40-F | 1,35 | 1,94 | 2,20 | - | - | - | - | - | - |
| 69B | IWF-5,2 | MW-40-R | 1,35 | 1,94 | 2,20 | - | - | - | - | - | - |
| 70A | Sarnafast SBF-6,0 | R75 | 1,32 | 1,42 | 1,42 | 0,72 | 1,42 | 32 | 5,0 | 0,35 | 0,58 |
| 71A | BS-4,8 | MW-40-F | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - |
| 71B | BS-6,1 | MW-40-F | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 |
| 72A | BS-4,8 | IR-82x40 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - |
| 72B | BS-6,1 | IRD-82x40 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$

²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$

³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$; minimum density = 400 kg/m³

Characteristic axial loading resistance $N_{R,k}$ [kN] for non-metallic substructures

| Combination | SFS intec flat roof fastener | Timber | | | Concrete EN 206-1 | | | Aerated Concrete DIN 4223-1 | | | Pumice Panel EN 1520 | | | |
|-------------|---------------------------------|--|---|---|----------------------|--------|---------------------------------|--------------------------------|-------|-------|---------------------------------|--------------|----------------------|--|
| | | OSB3 EN 300 $t \geq 18 \text{ mm}$ ¹⁾ | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}$ ²⁾ | Plywood EN 636 $t \geq 18 \text{ mm}$ ³⁾ | C12/15 | C25/30 | setting depth \geq [mm] | pre-drill diameter [mm] | P 3,3 | P 4,4 | setting depth \geq [mm] | IAC 6, D 1,0 | depth \geq [mm] | setting pre-drill diameter [mm] |
| 73A | T1-T25-6,3 | MW-40-F | - | - | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - | - | - |
| 73B | TS-T25-6,0 | MW-40-F | 1,31 | 1,43 | 2,30 | 0,44 | 0,89 | 32 | 5,0 | 1,07 | 1,78 | 75 | - | - |
| 74A | T1-T25-6,3 | IRD-8x2x40 | - | - | - | 1,83 | 1,83 | 20 | 5,0 | - | - | - | - | - |
| 74B | IWF-5,2 | IR-8x2x40 | 1,35 | 1,94 | 2,20 | - | - | - | 2,56 | 2,56 | 30 | - | - | - |
| 75A | Sarnafast SF-4,8 | Sarnabar | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - | - |
| 75B | Sarnafast SBF-6,0- | Sarnabar | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 | 75 | - | - |
| 76A | Sarnafast SBF-S- 6,0- | Sarnabar | 1,25 | 2,02 | 2,22 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 | 75 | - | - |
| 76B | IR2-4,8 | Sarnabar | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - | - |
| 77A | DT-4,8 | Sarnabar | - | - | - | 2,40 | 3,34 | 25 | 4,8 | - | - | - | - | - |
| 77B | DT-4,8 | Sarnabar Tube SBT-20 / Sarnabar | - | - | - | 2,10 | 2,10 | 25 | 4,8 | - | - | - | - | - |
| 78A | DT-S-4,8 | Sarnabar | - | - | - | 2,65 | 3,69 | 25 | 4,8 | - | - | - | - | - |
| 78B | DT-S-4,8 | Sarnabar Tube SBT-20 / Sarnabar | - | - | - | 2,10 | 2,10 | 25 | 4,8 | - | - | - | - | - |
| 79A | DT-6,3 | Sarnabar | - | - | - | 2,93 | 4,07 | 32 | 6,3 | - | - | - | - | - |
| 79B | DT-S-6,3 | Sarnabar | - | - | - | 2,23 | 3,10 | 32 | 6,3 | - | - | - | - | - |
| 80A | IW-S-5,0 | Sarnabar | 1,08 | 1,12 | 2,04 | - | - | - | - | - | - | - | - | - |
| 80B | IW-T-5,0 | Sarnabar | 1,08 | 1,12 | 2,12 | - | - | - | - | - | - | - | - | - |
| 81A | LBS-S-T25-8,0 | Sarnabar | - | - | - | - | - | - | 0,93 | 1,43 | 60 | - | - | - |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$

²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$

³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$; minimum density = 400 kg/m³

Characteristic axial loading resistance $N_{R,k}$ [kN] for non-metallic substructures

| Combination | SFS intec flat roof fastener | Timber | | | Concrete EN 206-1 | | | Aerated Concrete DIN 4223-1 | | | Pumice Panel EN 1520 | | |
|-------------|---------------------------------|--|---|---|----------------------|--------|---------------------------------|--------------------------------|-------|-------|---------------------------------|--------------|---------------------------------|
| | | OSB3 EN 300 $t \geq 18 \text{ mm}$ ¹⁾ | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}$ ²⁾ | Plywood EN 636 $t \geq 18 \text{ mm}$ ³⁾ | C12/15 | C25/30 | setting depth \geq [mm] | pre-drill diameter [mm] | P 3,3 | P 4,4 | setting depth \geq [mm] | LAC 6, D 1,0 | setting depth \geq [mm] |
| 81B | BS-S-6,1 | Fl-P-6,8 | 1,25 | 2,02 | 2,22 | - | - | - | - | - | - | - | - |
| 82A | BS-S-6,1 | Fl-P-16,0 / Fl-R-20 | 1,25 | 2,02 | 2,17 | - | - | - | - | - | - | - | - |
| 82B | LBS-S-T25-8,0 | IRD-82x40 | - | - | - | - | - | - | 0,93 | 1,44 | 60 | - | - |
| 83A | LBS-T25-8,0 | IRD-82x40 | - | - | - | - | - | - | 0,93 | 1,44 | 60 | - | - |
| 83B | LBS-T25-8,0 | IF/G-C-82x40 | - | - | - | - | - | - | 0,93 | 1,44 | 60 | - | - |
| 84A | IWF-5,2 | Fl-P-6,8 | 1,35 | 1,94 | 2,20 | - | - | - | - | - | - | - | - |
| 84B | IW-S-5,0 | Fl-P-6,8 | 1,08 | 1,12 | 2,04 | - | - | - | - | - | - | - | - |
| 85B | DT-4,8 | ID-70x70 | - | - | - | 2,40 | 2,56 | 25 | 4,8 | - | - | - | - |
| 86A | DT-6,3 | ID-70x70 | - | - | - | 2,93 | 3,68 | 32 | 6,3 | - | - | - | - |
| 86B | DT-4,8 | R75 | - | - | - | 1,39 | 1,39 | 25 | 4,8 | - | - | - | - |
| 87A | DT-S-4,8 | R75 | - | - | - | 1,39 | 1,39 | 25 | 4,8 | - | - | - | - |
| 88A | BS-4,8 | IPF45 / Fl-R-20 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - |
| 88B | BS-4,8 | IPF45 / Fl-R-20 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - |
| 89A | BS-4,8 | Isoftfast SQT | 1,45 | 1,32 | 1,45 | - | - | - | - | - | - | - | - |
| 89B | Sarnafast SF-4,8 | IF/G-C-82x40 | 1,45 | 1,32 | 2,18 | - | - | - | - | - | - | - | - |
| 90A | LBS-T25-8,0 | Sarnabar | - | - | - | - | - | - | 0,93 | 1,44 | 60 | - | - |
| 90B | Sarnafast SBF-6,0 | Sarnaweld disc 6,8 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 | 75 | - |
| 91A | Sarnafast SBF-6,0 | Sarnaweld disc 16 / Sarnabar Tube SBT-20 | 1,32 | 2,16 | 2,11 | 0,72 | 1,45 | 32 | 5,0 | 0,35 | 0,58 | 75 | - |
| 91B | Sarnafast SBF-S-6,0 | Sarnaweld disc 6,8 | 1,25 | 2,02 | 2,22 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 | 75 | - |
| 92A | Sarnafast SBF-S-6,0 | Sarnaweld disc 16 / Sarnabar Tube SBT-20 | 1,25 | 2,02 | 2,17 | 0,42 | 0,84 | 32 | 5,0 | 0,82 | 1,37 | 75 | - |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$

²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$

³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$; minimum density = 400 kg/m³

| | | Characteristic axial loading resistance $N_{R,k}$ [kN] for non-metallic substructures | | | | | | | |
|-------------|---------------------------------|---|---|---|------------------|---------------------------------|-------------------------------|-------------------------|---------------------------------|
| Combination | SFS intec flat roof fastener | Timber | | Concrete EN 206-1 | | Aerated Concrete DIN 4223-1 | | Pumice Panel EN 1520 | |
| | | OSB3 EN 300 $t \geq 18 \text{ mm}^1$ | Structural Timber EN 338 / C24 $t \geq 22 \text{ mm}^2$ | Plywood EN 636 $t \geq 18 \text{ mm}^3$ | C12/15 C25/30 | setting depth \geq [mm] | pre-drill diameter [mm] | P 3,3 P 4,4 | setting depth \geq [mm] |
| 92B | IR2-S-4,8 | Sarnabar | 1,28 | 1,74 | 1,94 | - | - | - | - |
| 93B | TI-6,3 | Sarnabar | - | - | - | 1,83 | 1,83 | 20 | 5,0 |
| 94A | IR2-4,8 | Sarnafast KT-82x40 | 1,45 | 1,32 | 2,18 | - | 2,73 | 3,79 | 30 |
| 94B | BSF-N-6,1 | RH45 | 1,32 | 1,54 | 1,54 | - | - | - | - |

¹⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$

²⁾ effective setting depth (penetration length of threaded part) $\geq 22 \text{ mm}$

³⁾ effective setting depth (penetration length of threaded part) $\geq 18 \text{ mm}$; minimum density = 400 kg/m³

SFS intec flat roof fasteners

Annex 109